

Dura Slideway Oil

Dura Slideway Oils are suitable for both vertical and horizontal slides and tables. The product is also suitable for headstocks and some gear boxes providing the viscosity is acceptable. Manufactured from high quality base stock to meet all the requirements modern machine tools ask of its lubricating oils.

FEATURES & BENEFITS

- ✓ Readily separate from all water based
- ✓ Polarised anti-wear additive package will adhere to all metal surfaces
- ✓ Non Tacky Additives
- ✓ Unique oil rejection Additives
- ✓ Multi functional across all types of machine tools



DESIGNED TO GIVE OUTSTANDING PERFORMANCE

Unlike traditional tacky slideway lubricants which often have the ability to emulsify readily into in-use emulsions – ultimately distorting refractometer readings and completely giving the impression that an in-use emulsion is up to strength when in fact it is not. Dura Slideway Lubricants meet a unique oil rejection test and will not distort refractometer readings of an in-use emulsion and will not contribute to tramp oil accumulation.

MULTI PURPOSE AS STANDARD

Dura Slideway Lubricants are suitable for both vertical and horizontal slides and tables. The product is also suitable for headstocks and some gear boxes providing the viscosity is acceptable.

TYPICAL PHYSICAL PROPERTIES

ISO Number	32	68	220
Specific Gravity	0.871	0.880	0.89
Flash Point (open) °C	220	220	220
Viscosity cSt at 100 °C	5.4	8.9	120
Viscosity cSt at 40 °C	31.9	68.5	220
Viscosity Index	105	100	100
Pour Point °C	-35	-30	-30