

Duracut ST (Range)

Duracut ST products are high performance, chlorine free neat cutting oil. Designed using a state of the art additive package blended together with highly refined base stock. This grade out performs all conventional neat oils. Ranging from 8 cSt to 32 cSt this range covers all neat oil requirements.

FEATURES & BENEFITS

- ✓ Anti-mist additives
- ✓ High Quality Mineral Oil
- ✓ Low Aromatic Content
- ✓ Low Viscosity
- ✓ High Flash Point
- ✓ High Lubricity, EP and Anti-wear Performance
- ✓ Prolonged tool life due to anti-wear technology
- ✓ Excellent Surface Finish



DESIGNED TO GIVE OUTSTANDING PERFORMANCE

Duracut ST Range are pale, low odour, chlorine free neat cutting oil containing extreme pressure additives, anti wear additives, lubricity additives and carefully selected mineral oils.

Designed specifically for use on sliding head CNC machines with through tool coolant. The various viscosities mean this range of products can be used on all applications including, gear cutting, grinding, honing, keyway cutting & broaching and general purpose metal working needs

MULTI PURPOSE AS STANDARD

Duracut ST range are multi-metal grades designed, for use on high tensile steels, stainless steel, alloys and all yellow metals

TYPICAL PHYSICAL PROPERTIES

ISO (cSt)	8	12	22	32
Appearance	Clear	Clear	Yellow	Yellow
Odour	None	None	None	None
Flash Point (°c)	>180	>200	>200	>200
Viscosity @ 40°c (cSt)	8.5	12.5	22	32
Chlorine	No	No	No	No