

Duralube AW Hydraulic Oil

A range of premium grade mineral based hydraulic oils with good anti-wear properties providing protection in the most demanding of systems. They are rust, corrosion and oxidation inhibited.

Performance Levels

- ✓ DIN 51524 Parts 1 and 2 (DIN 51525)
- ✓ Sperry Vickers I-286-S, M-2950-S
- ✓ Denison HF-2
- ✓ Cincinnati Milacron P-68, P-69, P-70



DESIGNED TO GIVE OUTSTANDING PERFORMANCE

Duralube AW Hydraulic Oils contain an effective anti-foam additive to control foam and facilitate the rapid release of entrained air, therefore maximising hydraulic system efficiency. They are miscible and fully compatible with all mineral hydraulic oils.

MULTI PURPOSE AS STANDARD

Duralube AW Hydraulic Oils are recommended for both industrial and off highway hydraulic systems. Other applications include: machining centre headstocks, centralised lubrication systems, power steering, compressors, suspension units, tipping gear, airline lubricators, jacks, PTO's etc.

TYPICAL PHYSICAL PROPERTIES

ISO Number	10	22	32	46	68	100
Specific Gravity	0.869	0.87	0.871	0.874	0.880	0.89
Flash Point (open) °C	210	220	220	240	240	240
Viscosity cSt at 100 °C	3.2	4.5	5.4	6.7	8.9	12.2
Viscosity cSt at 40 °C	10	22	31.9	44.1	68.5	100
Viscosity Index	100	105	105	100	100	100
Pour Point °C	-35	-35	-35	-35	-30	-30